

LA-UR-16-27760

Approved for public release; distribution is unlimited.

Title: Cosmic Ray Muon Tomography

Author(s): Durham, J. Matthew

Intended for: background slides for IAEA visitors

Issued: 2016-10-07






Cosmic Ray Muon Tomography

Matt Durham, *durham* @*lanl.gov* P-25 Subatomic Physics






Imaging with Muons







Verification of Dry Cask Storage



Layers of drift tubes record muon positions and trajectories before and after passing through cask UNCLASSIFIED

Ideal candidate for muon radiography:

- Cosmic ray muons can penetrate meters of heavy shielding
- Muon scattering angle is dependent on Z of materials
- External probe that is insensitive to neutron/gamma backgrounds from neighboring casks





2015 Measurement at INL

Muon trackers in weatherproof enclosures. One side elevated to increase muon flux through both detectors (falls off as \sim cos² Θ).



Westinghouse MC-10 cask, count time ~200 hrs UNCLASSIFIED






Imaging the Cask - Projection


Outside © 240 cm (q. s) 45

The detector field-of-view encompassed rows in the fuel basket with one, six, five and four assemblies. Since these are ~uniform in the vertical direction, project density image data onto horizontal axis

Journal of Nuclear Materials Management 44 3 (2016)

Clear difference across basket.












Ideal Detector Simulation


Ring detectors around cask measure muon tracks from all


azimuthal angles

GEANT4 simulation



Sinogram of cask









Reactor Imaging with Cosmic Ray Muons



Muon imaging at Fukushima - simulation





GEANT4 simulation. Results published in Physical Review Letters 109 152501 (2012).








Toshiba Muon Tracker – 7x7m² modules



Full muon tracker assembled and tested at Toshiba in Yokohama, Japan.


Options for deployment at Fukushima Daiichi power plant are being explored.






Proof of concept: Measurement at Toshiba CNA

-Effectively 1/10 scale demonstration of Fukushima reactor imaging











Toshiba CNA - Details














CNA Results – compare to simulation



GEANT4 Model of Reactor











Imaging the santa Maria del Fiore Cupola in Florence, Italy







Reinforcements in the Cupola

- Three pairs of *macigno* chains are believed to reinforce the Cupola.
 - Only the existence of the lowest pair have been proven.
- A wooden chain was also installed 7.75 m above the springing of the Cupola.
- Some scholars maintain that there are also iron chains inside the masonry.
 - Investigations with metal detectors have failed to yield conclusive evidence.
 - Thousands of Florentine pounds of iron (1 pound = 0.34 kg) were purchased during the construction of the dome.









Demonstration measurement at LANL

 We deployed our two muon tracker modules on two opposite sides of the wall and took data for 35 days.









Cupola demonstration measurement

Steel bars imaged through 2m of concrete







Data

Simulation





Treaty Verification



Application in Treaty Verification:

Slide 18

Los Alamos


NATIONAL LABORATORY

 Muon trackers and neutron detectors are placed over a submarine hull

 Coincident neutron/muon data recorded

Number of warheads reconstructed

The direction of cosmic ray tracks give a rough idea of SNM spatial extent. Sufficient information barrier? Further measurements needed.










Spatial discrimination of SNM

Z=-30 cm

Z=-40 cm







Z=-20 cm

Z=-10cm

